

EFST EXTRA FLEXIBLE CONDUIT

LFMC SEALTITE® EFST EXTRA FLEXIBLE CONDUIT



DESCRIPTION:

- Flexible metal core liquid tight conduit
- Designed for applications where no approvals are required
- Also available in black by special order
- Uses standard liquid tight connectors for easy installation
- Additional Put-ups available

SPECIFICATIONS:

- Galvanized steel core with liquid tight PVC jacket
- Color: Gray and Black
- Temp. range: -4°F to +176°F (-20°C to +80°C)
- UV (sunlight) resistant
- Corrosion resistant

APPLICATIONS:

- Applications requiring liquid tight, 1/4" ID
- Applications where no approvals are required

See: www.naed.org www.nema.org
www.anacondasealtite.com



Square-Locked Design
with cord packing 5/16" - 1-1/4"

Interlocked Design
1/4" and 1-1/2" - 6"



Trade Size (mm)	Item ID	Std. Pkg. (feet)	Inside Diameter (inches)		Outside Diameter (inches)		Bend Radius (inches)	Weight (lbs/100 ft)	Packages per Pallet
			Min	Max	Min	Max			
1/4"	35983	500 (reel)	0.245	0.260	0.445	0.460	1.8	14	3
	35981	500 (carton)							32
5/16" (10)	35993	100	0.390	0.405	0.560	0.575	2.0	15	48
	35991	500							32
3/8" (12)	36201	250	0.485	0.505	0.690	0.710	2.0	21	32
	36202	100							48
	36203	1500							3
	36204	800							3
1/2" (16)	36211	200	0.620	0.640	0.820	0.840	2.5	25	32
	36212	100							48
	36213	1000							3
	36214	500							4
3/4" (21)	36222	100	0.815	0.835	1.030	1.050	3.0	39	32
	36226	1000							3
	36228	500							3
1" (27)	36231	100	1.030	1.055	1.290	1.315	4.0	51	24
	36238	400							3
1-1/4" (35)	36241	50	1.370	1.395	1.635	1.660	4.5	66	24
	36248	250							3
1-1/2" (41)	36251	50	1.575	1.600	1.865	1.900	5.5	104	10
	36254	150							3
2" (53)	36261	50	2.020	2.045	2.340	2.375	7.0	136	10
	36268	100							3
2-1/2" (63)	34272	25	2.480	2.505	2.840	2.875	9.5	182	3
3" (78)	34281	25	3.070	3.100	3.460	3.500	15.0	255	15
3-1/2" (89)	34301	25	3.500	3.540	3.960	4.000	16.0	314	6
4" (103)	34291	25	4.000	4.040	4.460	4.500	17.0	363	6
5" (127)	36351	25	4.975	5.035	5.505	5.565	22.0	534	5
6" (152)	36361	25	6.015	6.075	6.565	6.625	30.0	666	3

FITTINGS FINDER



IP 66/67 with approved fittings

METALLIC
SEALTITE®

E
F
S
T