

HC HOT AND COLD RESISTANT CONDUIT

LFMC SEALTITE® HC HIGH TEMPERATURE FLEXIBLE CONDUIT



DESCRIPTION

- Flexible metal core liquid tight conduit
- Designed for applications where a higher temperature range is needed and where agency approvals are not required
- Manufactured in a full range of trade sizes from 3/8" through 4"
- Uses standard liquid tight connectors for easy installation

SPECIFICATIONS

- Galvanized steel core with cord packing (size 3/8 to 1-1/4") and a liquid tight PVC jacket
- Color: Gray and Black
- Temp. range: -51°F to +221°F (-46°C to +105°C)
- UV (sunlight) resistant
- Corrosion resistant

APPLICATIONS

- Applications for high and low temperature where UL and CSA approvals are not required
- Steel and petrochemicals industries

See: www.naed.org www.nema.org
www.anacondasealtite.com



Square-Locked Design string packing 3/8" - 1-1/4"

Interlocked Design 1-1/2" - 4"



Trade Size (mm)	Item ID	Std. Pkg. (feet)	Inside Diameter (inches)		Outside Diameter (inches)		Bend Radius (inches)	Weight (lbs/100 ft)	Packages per Pallet
			Min	Max	Min	Max			
3/8" (12)	37202	100	0.485	0.505	0.690	0.710	2.0	21	48
	37204	800							3
1/2" (16)	37212	100	0.620	0.640	0.820	0.840	2.5	25	48
	37214	500							4
3/4" (21)	37222	100	0.815	0.835	1.030	1.050	3.0	39	32
	37228	500							3
1" (27)	37231	100	1.030	1.055	1.290	1.315	4.0	51	24
	37238	400							3
1-1/4" (35)	37241	50	1.370	1.395	1.630	1.660	4.5	66	24
	37248	250							3
1-1/2" (41)	37251	50	1.575	1.600	1.865	1.900	5.5	104	10
	37254	150							3
2" (53)	37261	50	2.020	2.045	2.340	2.375	7.0	136	10
	37268	100							3
3" (78)	37281	25	3.070	3.100	3.460	3.500	15.0	255	15
4" (103)	37291	25	4.000	4.040	4.460	4.500	17.0	362	6

FITTINGS FINDER



IP 66/67 with approved fittings

METALLIC
SEALTITE®

H
C