

HGX EXTREME TEMPERATURE, ZERO HALOGEN CONDUIT

LFMC SEALTITE® HGX EXTREME TEMPERATURE, ZERO HALOGEN FLEXIBLE CONDUIT



DESCRIPTION

- Flexible metal core liquid tight conduit
- The Halogen free jacket provides protection from toxic gas emission
- Designed for extreme temperature applications where superior resistance to temperature ranges is required. (-76°F to +302°F)
- Available standard in black
- Uses standard liquid tight connectors for easy installation

SPECIFICATIONS

- Galvanized steel core with liquid tight TPE jacket
- Color: Black
- Temp. range: Static installations -76°F to +302°F (-60°C to +150°C). Dynamic installations at atmospheric pressure rated for -76°F to +221°F (-60°C to +105°C)
- UV (sunlight) resistant
- Extra corrosion resistant
- Oil resistant

APPLICATIONS

- Extreme duty applications
- Extreme high or low temperature requirements
- Applications where no approvals are required

See: www.naed.org www.nema.org
www.anacondasealtite.com



Square-Locked Design with cord packing 3/8" - 1-1/4"

Interlocked Design 1-1/2" - 4"



Trade Size (mm)	Item ID	Std. Pkg. (feet)	Inside Diameter (inches)		Outside Diameter (inches)		Bend Radius (inches)	Weight (lbs/100 ft)	Packages per Pallet
			Min	Max	Min	Max			
3/8" (12)	39102	100	0.485	0.505	0.690	0.710	2.0	21	48
1/2" (16)	39112	100	0.620	0.640	0.820	0.840	2.5	25	48
3/4" (21)	39122	100	0.815	0.835	1.030	1.050	3.0	39	32
1" (27)	39131	100	1.030	1.055	1.290	1.315	4.0	51	24
1-1/4" (35)	39141	50	1.370	1.395	1.635	1.660	4.5	66	24
1-1/2" (41)	39151	50	1.575	1.600	1.865	1.900	5.5	104	10
2" (53)	39161	50	2.020	2.045	2.340	2.375	7.0	136	10
2-1/2" (63)	39171	50	2.480	2.505	2.840	2.875	9.5	182	3
3" (78)	39181	25	3.070	3.100	3.460	3.500	15.0	255	15
4" (103)	39191	25	4.000	4.040	4.460	4.500	17.0	363	6

FITTINGS FINDER



IP 66/67 with approved fittings