

HFSS ZERO HALOGEN, LOW SMOKE, LOW FLAME, STAINLESS STEEL CONDUIT

LFMC SEALTITE® HFSS
ZERO HALOGEN, LOW SMOKE, LOW
FLAME 316 STAINLESS STEEL CONDUIT



SPECIFICATIONS

- 316 stainless steel core with liquid tight TPU jacket
- Color: Black
- Temp. range: -40°F to +176°F (-40°C to +80°C)
- UV (sunlight) resistant
- Corrosion resistant

APPLICATIONS

- Commercial and transport applications where Zero Halogen and Low Smoke conduit is specified

DESCRIPTION

- The continuously interlocked, 316 stainless steel core provides exceptional crush and corrosion resistance
- Durable, sunlight resistant, flame retardant, low smoke and Zero Halogen TPU jacket resists heat, oil and chemical breakdown
- Designed for most extreme temperature applications
- Meets or exceeds: ASTM-E162 (Flame spread); ASTM-E662 (Smoke density); Bombardier SMP-800C (Toxic gas generation)

See: www.naed.org www.nema.org
www.anacondasealtite.com



Square-Locked Design with cord packing 3/8" - 1-1/4"

Interlocked Design 1-1/2" - 2"



Trade Size (mm)	Item ID	Std. Pkg. (feet)	Inside Diameter (inches)		Outside Diameter (inches)		Bend Radius (inches)	Weight (lbs/100 ft)	Packages per Pallet
			Min	Max	Min	Max			
3/8" (12)	49802	100	0.484	0.504	0.690	0.710	2.0	22	48
1/2" (16)	49812	100	0.622	0.642	0.820	0.840	2.5	24	48
3/4" (21)	49822	100	0.820	0.840	1.030	1.050	3.0	36	32
1" (27)	49831	100	1.041	1.066	1.290	1.315	4.0	50	24
1-1/4" (35)	49841	50	1.380	1.410	1.630	1.660	4.5	66	24
1-1/2" (41)	49851	50	1.575	1.600	1.865	1.900	5.5	98	10
2" (53)	49861	50	2.020	2.045	2.340	2.375	7.0	130	10

FITTINGS FINDER



IP 66/67 with approved fittings