

MTC MACHINE TOOL CONDUIT

LFMC SEALTITE® MTC MACHINE TOOL EXTRA FLEXIBLE CONDUIT



SPECIFICATIONS

- Galvanized steel core with liquid tight PVC jacket
- Color: Black
- Temp. range: -4°F to +140°F (-20°C to +60°C)
- UV (sunlight) resistant
- Corrosion resistant
- Tight bend radius

APPLICATIONS

- High flexibility
- Machine tool industry

DESCRIPTION

- Flexible metal core liquid tight conduit
- Designed for Machine Tool industry for high flexibility
- Very tight bend radius making installation easier
- Uses standard liquid tight connectors for easy installation

See: www.naed.org www.nema.org



Square-Locked Design
3/8" - 2"



Trade Size (mm)	Item ID	Std. Pkg. (feet)	Inside Diameter (inches)		Outside Diameter (inches)		Bend Radius (inches)	Weight (lbs/100 ft)	Packages per Pallet
			Min	Max	Min	Max			
3/8" (12)	38302	100	0.484	0.505	0.679	0.704	1.5	16	48
	38304	800							3
1/2" (16)	38312	100	0.622	0.640	0.818	0.843	2.0	20	48
	38314	500							4
3/4" (21)	38322	100	0.820	0.835	1.009	1.034	2.5	24	32
	38328	500							3
1" (27)	38331	100	1.041	1.055	1.228	1.258	3.0	30	24
	38338	400							3
1-1/4" (35)	38341	50	1.380	1.395	1.565	1.595	3.5	40	24
	38348	250							3
1-1/2" (41)	38351	50	1.575	1.600	1.830	1.860	4.0	70	24
	38354	150							3
2" (53)	38361	50	2.020	2.045	2.270	2.300	5.0	87	10
	38368	100							3

FITTINGS FINDER



IP 65 with approved fittings

METALLIC
SEALTITE®

M
T
C