

METRIC NICKEL-PLATED BRASS FITTINGS

LFMC ISO SEALTITE® COMPACT FITTINGS METRIC NICKEL-PLATED BRASS PREMIUM FITTINGS



DESCRIPTION

- New compact design: 20% smaller and 35% lighter than standard SEALTITE® fittings
- Ideal for tight spaces
- Excellent corrosion resistance, strength and durability
- IP 66/67 rated when installed with approved conduit and tightened to UL-514B/CSA C22.2 18.3 torque specifications
- Approved for both exposed and concealed locations

SPECIFICATIONS

- Nickel-Plated Brass with PA6 clamping ring
- Each fitting has an O-ring
- Color: Metallic
- Temp. range: -49°F to +221°F (-45°C to +105°C)
- cULus 514B Approved DWTT.E234207, complies with NEMA standard FB-1

APPLICATIONS


- Metallic flexible conduit
- Compact design ideal for tight spaces
- High-end appearance for good presentation
- Suitable for hazardous locations per NEC Articles
 - 501.10 (B) (2) Class I Div. 2
 - 502.10 (A) (2) and (B) (2) Class II Div. 1 & 2
 - 503.10 (A) (3) and (B) Class III Div. 1 & 2

See: www.ul.com www.nfpa.org
www.naed.org www.nema.org
www.anacondasealtite.com

STRAIGHT




Trade Size	Thread ISO	Item ID	Min. Int. Bore	Dimensions mm				Weight (lbs/100)	Std. Pkg.
				A	B	C	E		
3/8"	M16 x 1.5	7120161IT	11.0	31	10	26	24	10.8	10
3/8"	M20 x 1.5	7120171IT	11.0	31	10	26	24	10.8	10
1/2"	M20 x 1.5	7120201IT	14.5	32	10	29	27	12.1	10
3/4"	M25 x 1.5	7120251IT	19.4	33	10	35	33	17.2	10
1"	M32 x 1.5	7120321IT	24.7	36	12	45	42	30.6	5
1-1/4"	M40 x 1.5	7120401IT	33.3	40	13	53	52	41.0	2
1-1/2"	M50 x 1.5	7120501IT	38.0	46	14	62	60	61.7	2
2"	M63 x 1.5	7120631IT	49.0	52	16	76	72	97.0	2



90 DEGREE



Trade Size	Thread ISO	Item ID	Min. Int. Bore	Dimensions mm					Weight (lbs/100)	Std. Pkg.
				A	B	C	D	E		
3/8"	M16 x 1.5	7129161IT	11.0	26	10	26	31	24	19.2	10
3/8"	M20 x 1.5	7129171IT	11.0	26	10	26	32	24	19.2	10
1/2"	M20 x 1.5	7129201IT	14.5	28	10	29	34	27	22.3	10
3/4"	M25 x 1.5	7129251IT	19.4	32	10	35	40	33	36.8	4
1"	M32 x 1.5	7129321IT	24.7	40	12	45	49	42	65.3	5
1-1/4"	M40 x 1.5	7129401IT	33.3	46	13	53	53	52	95.2	4
1-1/2"	M50 x 1.5	7129501IT	38.0	52	14	62	57	60	131.2	2
2"	M63 x 1.5	7129631IT	49.0	62	16	76	68	72	206.4	2



IP 66/67 with approved conduit