

NMEF TYPE B NON-METALLIC PROTECTIVE TUBING, CSA APPROVED

NMPT-B SEALTITE® NMEF (TYPE B)
NON-METALLIC FLEXIBLE TUBING



DESCRIPTION

- Non-metallic Type B liquid tight tubing
- Designed for OEM and industrial applications
- Uses special non-metallic connectors for easy installation.
- Can also be used with a liquid tight connector
- Additional Put-ups available

SPECIFICATIONS

- Smooth Inner Wall PVC with a Co-Extruded Reinforcing PVC Coil
- Extra flexible
- Color: Black
- Temp. range: -17°F to +176°F (-27°C to +80°C)
- UV (sunlight) resistant
- Oil resistant
- CSA Approved

APPLICATIONS

- OEM machine building
- Industrial applications where tight bend radius is required

See: www.csa-international.org
www.anacondasealtite.com



Smooth Inner Wall PVC with a Co-Extruded Reinforcing PVC Coil 3/8" - 2"



Trade Size (mm)	Item ID	Std. Pkg. ft	Inside Diameter (inches)		Outside Diameter (inches)		Bend Radius (inches)	Weight (lbs/100 ft)	Packages per Pallet
			Min	Max	Min	Max			
3/8" (12)	3620120	100	0.484	0.504	0.690	0.710	0.8	9	48
1/2" (16)	3620160	100	0.622	0.640	0.820	0.840	0.9	11	28
3/4" (21)	3620200	100	0.820	0.840	1.030	1.050	1.0	13	24
1" (27)	3620260	100	1.041	1.066	1.290	1.315	1.4	20	20
1-1/4" (35)	3620350	100	1.380	1.410	1.630	1.660	1.7	22	20
1-1/2" (41)	3620400	50	1.575	1.600	1.865	1.900	2.0	27	20
2" (53)	3620500	50	2.020	2.045	2.340	2.375	8.0	45	10

FITTINGS FINDER



IP 66/67 with approved fittings