

OR OIL RESISTANT CONDUIT

LFMC SEALTITE® OR OIL RESISTANT FLEXIBLE CONDUIT



DESCRIPTION:

- Flexible metal core liquid tight conduit
- Designed for applications that need superior resistance to petroleum, synthetic oils and chemical degradation
- Uses standard liquid tight connectors for easy installation

SPECIFICATIONS

- Galvanized steel core with liquid tight PVC jacket
- Color: Black
- Temp. range: -9°F to +221°F (-23°C to +105°C)
- UV (sunlight) resistant
- Corrosion resistant
- Extra oil resistant

APPLICATIONS

- Extreme resistance to oil
- Petrochemical and steel industries
- Applications where no approvals are required

See: www.naed.org www.nema.org
www.anacondasealtite.com



Square-Locked Design with
cord packing 3/8" - 1-1/4"

Interlocked Design 1-1/2" - 2"



Trade Size (mm)	Item ID	Std. Pkg. (feet)	Inside Diameter (inches)		Outside Diameter (inches)		Bend Radius (inches)	Weight (lbs/100 ft)	Packages per Pallet
			Min	Max	Min	Max			
3/8" (12)	36602	100	0.485	0.505	0.690	0.710	2.0	21	48
	36604	800							3
1/2" (16)	36612	100	0.620	0.640	0.820	0.840	2.5	25	48
	36614	500							4
3/4" (21)	36622	100	0.815	0.635	1.030	1.050	3.0	39	32
	36628	500							3
1" (27)	36631	100	1.030	1.055	1.290	1.315	4.0	51	24
	36638	400							3
1-1/4" (35)	36641	50	1.370	1.395	1.635	1.660	4.5	66	24
	36648	250							3
1-1/2" (41)	36651	50	1.575	1.600	1.865	1.900	5.5	104	10
	36654	150							3
2" (53)	36661	50	2.020	2.045	2.340	2.375	7.0	136	10
	36668	100							3

FITTINGS FINDER



IP 66/67 with approved fittings