

TYPE A METALLIC FITTINGS FOR CNP CONDUIT UL LISTED AND CSA APPROVED

LFNC TYPE A FITTINGS FITTINGS FOR CNP TYPE A CONDUIT (ONLY) ZINC-PLATED STEEL



DESCRIPTION

- Type A fitting approved for use solely with SEALTITE® CNP flexible conduit
- Three-piece, zinc-plated steel (the gland nut and captive collar are two pieces)
- The grooved end of a plastic ferrule goes in conduit and the hexagonal opposite end engages the fitting body
- Each fitting has a sealing ring and lock nut
- The throat of the fitting has a plastic insulator
- UL and CSA approved

SPECIFICATIONS

- Zinc-plated steel, plastic and an elastomer seal
- Corrosion resistant, strong and durable
- Color: Metallic
- UL 514B Approved #E472179
- CSA Approved #065178e
- Temp. range: -49°F to +221°F (-45°C to +105°C)




See: www.ul.com www.csa-international.org
www.nfpa.org www.naed.org www.nema.org
www.anacondasealtite.com

STRAIGHT




Trade Size	Item ID	Dimensions (inches)			KO Size NPT	Weight (lb/Pkg)	Std. Pkg.
		A	B	C			
3/8"	5STNM38	2.156	0.594	1.156	1/2"	5.6	25
1/2"	5STNM50	2.594	0.594	1.313	1/2"	8.1	25
3/4"	5STNM75	2.594	0.594	1.625	3/4"	11.0	25
1"	5STNM100	2.875	0.719	1.938	1"	3.2	5
1-1/4"	5STNM125	3.406	0.750	2.406	1-1/4"	6.0	5
1-1/2"	5STNM150	3.438	0.750	2.781	1-1/2"	3.0	2
2"	5STNM200	3.969	0.750	3.375	2"	2.4	1



90 DEGREE



Trade Size	Item ID	Dimensions (inches)				KO Size NPT	Weight (lb/Pkg)	Std. Pkg.
		A	B	C	D			
3/8"	5STNM9038	1.25	0.594	1.156	2.03	1/2"	7.5	25
1/2"	5STNM9050	1.28	0.594	1.313	2.38	1/2"	9.5	25
3/4"	5STNM9075	1.44	0.594	1.625	2.5	3/4"	5.5	10
1"	5STNM90100	1.75	0.719	1.938	2.75	1"	4.1	5
1-1/4"	5STNM90125	1.97	0.750	2.406	3.47	1-1/4"	7.7	5
1-1/2"	5STNM90150	2.25	0.750	2.781	3.59	1-1/2"	4.0	2
2"	5STNM90200	2.53	0.750	3.375	4.41	2"	3.1	1



NON-METALLIC
SEALTITE®

T
Y
P
E
A